RESEARCH ARTICLE

Open Access

Induced seismicity in EGS reservoir: the creep route

Jean Schmittbuhl^{1*}, Olivier Lengliné¹, François Cornet¹, Nicolas Cuenot² and Albert Genter³

*Correspondence: jean.schmittbuhl@unistra.fr ¹EOST, Université de Strasbourg/CNRS, 5 rue René Descartes, 67000 Strasbourg, France Full list of author information is available at the end of the article

Abstract

Background: Observations in enhanced geothermal system (EGS) reservoirs of induced seismicity and slow aseismic slip ruptures on related faults suggest a close link between the two phenomena.

Methods: We base our approach on the case study of the EGS site of Soultz-sous-Forêts where seismicity has been shown in particular during the 1993 stimulation to be induced not only by fluid pressure increase during stimulation but also by aseismic creeping effects. We propose an interpretation of the field observations of induced seismicity using a laboratory experiment that explores, in great detail, the deformation processes of heterogeneous interfaces in the brittle-creep regime. We track the evolution of an interfacial crack over 7 orders of magnitude in time and 5 orders of magnitude in space using optical and acoustic sensors.

Results: We show that a creep route for induced seismicity is possible when heterogeneities exist along the fault. Indeed, seismic event occurrences in time and space are in strong relation with the development of the aseismic motion recorded during the experiments. We also infer the statistical properties of the organization of the seismicity that shows strong space-time clustering.

Conclusions: We conclude that aseismic processes might drive seismicity besides the classical effects related to fluid pressure and show that a creep route for induced seismicity is possible.

Keywords: Induced seismicity; Fault asperities; Brittle-creep; Asperity pinning; Soultz-sous-Forêts

Background

The exploitation of a geothermal reservoir can lead to the occurrence of an abundant seismicity, particularly during phases of hydraulic stimulation. This seismicity has a strong societal impact, as it can be felt by the population, especially in densely populated area as in Europe, e.g., $M_L = 3.4$, Basel, 2006 (Häring et al. 2008). Reducing this impact is thus one of the main challenges in the development of geothermal energy production. In order to understand the mechanical processes responsible for seismic activity, all possible mechanisms for induced seismicity have to be studied (Majer et al. 2007). Among them the link between earthquakes and aseismic deformations is only at a starting state (Cornet et al. 2007; Bourouis and Bernard 2007). Deciphering this link between seismicity and aseismic motion can not only help to mitigate the risk posed by seismicity but also



© 2014 Schmittbuhl et al.; licensee Springer. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/2.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly credited.

help to monitor and model the evolution of the geothermal reservoir. The mechanism relating earthquakes and aseismic processes is still elusive due to the difficulty of imaging these phenomena with large spatiotemporal variability at depth. However, a good example of joint seismic and aseismic deformation has been obtained at the enhanced geothermal system (EGS) site of Soultz-sous-Forêts (France) (Genter et al. 2010) in particular during the 1993 water injection experiment for stimulation of the naturally fractured granite reservoir below 2,500 m.

Fluid-induced seismicity at Soultz-sous-Forêts

Seven large-scale fluid injections have been performed at Soultz-sous-Forêts on the four deep wells: GPK1 was stimulated in 1993, GPK2 in 1994 and 1995 for the upper reservoir and 2000 for the deep reservoir, GPK3 in 2003, and GPK4 in 2004 and 2005 (Dorbath et al. 2009; Huenges and Ledru 2010). During all these stimulations, induced seismicity has been extensively studied (Charléty et al. 2007; Cuenot et al. 2008). For all of them, fluid pressure increase has been considered as the main source of seismicity initiation (Shapiro et al. 1999). The 1993 stimulation is certainly the first stimulation for which a precise influence of the fluid pressure has been demonstrated (Cornet et al. 1997; Cornet et al. 2007). Figure 1 reproduces the main results that have been obtained. Interpretation in the Mohr space relies on the difference between Coulomb's failure criterion of an initially intact material (i.e., a yield criterion for the initiation) and the friction law (see Figure 1a) (Burov 2009; Jaeger et al. 2009) on existing interfaces. Typically, when the fluid pressure p is increased, the effective normal stress σ^e is reduced and the material reaches first the friction criterion (in green in Figure 1a) if pre-existing fractures exist and are favorably oriented within the local stress field. In this case, a shear slip, or hydro-shear, is initiated related to radiated waves well characterized by an earthquake double-couple solution. This process explains very well the onset of seismicity at the bottom of the stimulated zone (below 3000 m see Figure 1b,c). The orientation of the seismic cloud with respect to the maximum horizontal stress orientation gives the friction angle $\phi \approx 30^\circ$, i.e., a static friction coefficient $\mu \approx 0.60$. Because of dilatancy of the fracture during shear offset, permeability is significantly and permanently increased during hydro-shear. At higher flow rates $(\geq 18 \text{ l/s})$, pressure stabilizes to a plateau for which seismicity migrates upwards along the maximum horizontal stress direction (in red in Figure 1b,c). During that regime, the effective stress is supposed to be so low that Coulomb's failure criterion has been passed (in red in Figure 1a) and hydro-frac is initiated. Fractures are then expected to be perpendicular to the minimal principal horizontal stress with little shear offset and a poor permeability enhancement without the use of proppant (Huenges and Ledru 2010). An alternative scenario would occur if no pre-existing fractures are optimally oriented. Then, a fresh new shear fracture might be initiated following the failure of Coulomb's criterion (in blue in Figure 1a, in the domain above Byerlee's criterion in blue) along the $\tau = c' + \sigma' \tan \phi'$ line. In that case, the orientation of the cloud should be closer to the maximum principal stress direction. Indeed, the internal friction coefficient ϕ' is typically larger than the friction coefficient of Byerlee's law. Such orientation of the seismic cloud has been observed for the very basal part of the stimulated reservoir suggesting that the initiation of a new fracture might have existed there.

Schmittbuhl *et al. Geothermal Energy* 2014, **2**:14 www.geothermal-energy-journal.com/content/2/1/14



Aseismic slip at Soultz-sous-Forêts

Aseismic slips in a deep geothermal reservoir were first observed at Soultz-sous-Forêts by (Cornet et al. 1997). They showed that after the two stimulations of GPK1 performed in September and October 1993, the borehole has been shifted at several depths just below the casing shoe at 2,857 m. From ultrasonic borehole images between 2,853 and 3,104 m before and after the two consecutive hydraulic injections of fresh water, cumulating up to 44,000 m³, they evidenced fresh displacements along existing fractures between 2,867 and 2,976 m that were of the order of several millimeters to several centimeters. One of the largest offset was measured at 2,925 m (fault F): 4.3 cm and considered as part of a significant fault zone of the reservoir with a quasi-vertical fault plane (dip of 86° and a dip direction of N48° (Cornet et al. 1997)) (see Figure 2). Interestingly, this fault zone is not part of the major fault zones observed during borehole logging (Sausse et al. 2010). Borehole logging shows that it is largely filled with secondary minerals like illite which might influence the friction properties of the fault (Genter et al. 1997). An important complementary observation is the seismicity recorded during the injection period corresponding to the occurrence of the borehole offset.



Indeed, 165 events were recorded from the surface network which was far much less than the number of events recorded by the borehole down-hole network (20,000 events) (Helm 1996). They showed however that the magnitude of the largest recorded event was $M_L = 1.9$ corresponding to a seismic moment M_0 of 5.4×10^{11} Nm and a rupture area of typically d = 50 m for a stress drop of 9 MPa (assuming a circular crack embedded in an elastic isotropic medium and a shear modulus of $\mu = 20$ GPa) consistently with observations in similar contexts (Abercrombie and Leary 1993). From general scaling laws (Kanamori and Anderson 1975), the expected slip D from this largest event would be of the order of 1 cm: $D = 4M_0/\pi \mu d^2$ which is significantly smaller than the measured offset in the borehole. (Cornet et al. 1997) concluded that the large slips evidenced in the borehole could not be explained by the recorded earthquakes. Subsequently, they proposed that these large slips are aseismic which was the first indirect observation of aseismic slip induced by a fluid injection at Soultz-sous-Forêts EGS.

Micro-seismicity during aseismic slip at Soultz-sous-Forêts

(Bourouis and Bernard 2007) re-explored 10 years after these outstanding observations trying to conduct a fine analysis of the micro-seismicity during the injection period. They used a multiplet approach and relocated up to 400 events within the fault zone where aseismic slip was observed. The location accuracy was of the order of 1 m and they obtained 30 multiplets or families of similar events within the fault zone. An interesting observation is that the rupture size for all these events is of the order of d = 10 m. From their observations, they inferred three important conclusions. First, events within a multiplet were located within the same rupture zone which showed that the same asperity was reloaded and broken several times during the injection period. The second conclusion is that several asperities along the fault were ruptured at the same time during the injection. Third, the cumulative slip at each asperity through several ruptures was consistent with the borehole offset measurement. The conclusion is a clear image of the fault behavior during loading: the fault undergoes a large aseismic slip which triggers multiple local asperity failures.

The goal of the present paper is to propose a mechanical model of this fault behavior. To do so, we developed an experimental approach to mimic the response of a single fault when submitted to a global slow rupture propagation but locally unstable at asperities where micro-seismic activity is triggered. The model is analogous and incorporates a large space and time dynamics: 7 orders of magnitude in time and 5 orders of magnitude in space. A numerical approach would be difficult with such a large range of timescales and wavelengths (Kaneko et al. 2010).

Methods

An analogous fault model with random asperities

Samples are made of transparent Plexiglas which provides optical access to the rupture propagation. The analogous fault model is obtained by annealing two plates of $20 \times 10 \times 1 \text{ cm}^3$ and $23 \times 2.8 \times 0.5 \text{ cm}^3$ at 190°C for 45 min which is significantly above the glass transition of the material but below the melting point. Under normal load, the two plates get in close contact and stick together along a relatively weak plane (weaker than the bulk) (Schmittbuhl and Måløy 1997). The goal is to study the collective behavior of multiple

asperities when a slow crack propagates and locally pins. For this, we sandblast one of the plates before the annealing procedure to induce random local toughness fluctuations (Lengliné et al. 2011b). Sandblasting is obtained using (180 to 300 μ) particles, an air pressure of 3 bars for 4 min at a blowing distance of 20 to 40 cm (Grob et al. 2009).

A subcritical rupture propagation

Samples with a weak plane along which the toughness is fluctuating but with an average toughness lower than that of the bulk are submitted to a slow cantilever loading (mode I) (see Figure 3) (Lengliné et al. 2012). This configuration differs from a shear mode (mode II or III) of a fault configuration, but similarities in the stress intensity formulation exist and analogies can be established to extend the results to other loading conditions (Schmittbuhl et al. 2003).

The loading includes different phases: firstly, the plate is loaded by the slowly imposed displacement of the loading rod (see left side of Figure 3a) at a low constant speed up to the initiation of the fracture. At some point, the displacement rate is suddenly increased (see



Figure 4b), and the crack propagates over a few millimeters at quasi-constant velocity. The loading rate is of the order of 0.4 mm/s during this acceleration phase. The mechanical response, i.e., the force undergone by the plate during the experiment, is then recorded (Figure 4a). The setup being at imposed displacement, the crack propagation is stable and the average rupture velocity is controlled by the loading rate in the subcritical regime. Lastly, the loading rate is reduced, and the fracture propagates owing to the relaxation of the rupture at a decreasing speed (Lengliné et al. 2011a).

Optical monitoring of the fracture front

Taking images at high resolution (from 1 Mpixels with the fast camera up to 12 Mpixels with the SLR digital camera), we can obtain a precise spatial description of the fracture front (see Figure 5). It is observed that Fourier analysis of the front shows a power law behavior of the power spectrum over more than two decades with a roughness exponent H = 0.6 (Lengliné et al. 2011b; Schmittbuhl and Måløy 1997; Schmittbuhl et al. 2003).

Acoustic emissions during fracture propagation

From the acoustic sensors, acoustic emissions are recorded at 5 M samples/s (sampling time is $0.2 \ \mu$ s) for up to 30 s (*cf.* the duration of each experiment). Figure 6 shows an example of such an acoustic event. During the acoustic acquisition, the fast camera is shooting at a frame rate of 1,000 images/s (i.e., time delay between images is 1 ms) which is much lower than the sampling rate of the acoustic acquisition. As a consequence, recorded acoustic events have a much higher temporal resolution than optical events. In contrast,





spatial resolution of optical events is much higher than that of acoustic events. Moreover, duration of acoustic events is also very different from those of optical events. The former never exceeded 100 μ s. On the contrary, the latter could last up to several seconds at the largest scale. The overall observation is that numerous acoustic events are triggered during a single large-scale optical event. It suggests that we directly observe a simultaneous aseismic and seismic deformation along the crack front.

Locations of acoustic events are obtained using a beam-forming procedure. Because of the large number of waveforms (up to 64 sensors) and the continuous recording at very high frequency (5 MHz), we introduced an array-processing scheme for locating the source of the acoustic emissions. We define a grid domain over which we search for the possible location of the events. For each position of the grid we compute the expected arrival times of the event at each recorder assuming a homogeneous medium and straight ray path. We then shift each waveform according to these computed arrival times. Signals from all shifted waveform are stacked, and we finally keep the stacked signal around the first arrival. If the computed delay corresponds to the one for the true position of the source, we expect to have a very good match of all waveforms. We finally use the amplitude of this stack as a measure of the probability of the event location. An example of the location of one event is shown in Figure 7.





Results and discussion

Figure 8 shows the evolution of the locations of the acoustic emissions during one experiment where the fracture front advances by 1 cm. We are able to follow the front advance during its propagation even if the spatial resolution of the acoustic location is significantly larger than the optical resolution.

During each experiment, i.e., the propagation of the fracture front over several millimeters, we recorded several hundreds of acoustic emissions. Figure 9 shows a distribution of the energy recorded for each event. A first simple calibration provides an estimate of the absolute energy of the order of 10^{-11} to 10^{-8} J per events. Magnitude estimates of these events are then in the range -10 to -8 using the classical energy-magnitude relation from (Kanamori and Anderson 1975): M = 2/3Log(E) - 3.2. Figure 9 shows that a power law behavior exists over two decades of energy consistently with Gutenberg-Richter distribution.

Combining aseismic and seismic events

An imposed loading perturbation To go one step further in understanding the link between acoustic emission and local creep events, we took advantage of the experimental configuration to introduce a perturbation in the loading and look for the response of the system. Figure 4 shows how this perturbation is introduced in the loading rate. We observed that the average position of the fracture front follows exactly the perturbation of the loading frame after a small shift in time. The force decreases as the front velocity increases which is a velocity weakening effect.



Following the crack front advance with the digital camera as described in the 'Methods' section, we are able to monitor the local speed of the front (Grob et al. 2009; Måløy et al. 2006). We see in Figure 10 that the overall trend of the experiment is imaged by the general evolution of the color: slightly blue at the beginning (long waiting time corresponding to low speed), becoming very red (shorter waiting time corresponding to higher speed), and back to mostly blue during the speed reduction of the front. The interesting part is the details of the local velocity. Clearly patches of increased speeds (red patches) exist. By thresholding at ten times the average velocity of the front, the image of the local velocity field, we obtained a set of 'optical' events that are significantly faster than the loading speed but also significantly slower than the dynamical rupture velocity





(i.e., Rayleigh speed). These zones correspond to aseismic events which are accelerated advances compared to the average speed.

An interesting observation is that local velocities are distributed as a unique power law on a broad range of velocities (more than 3 orders of magnitude): $P(v) \propto v^{-2.55}$ (Måløy et al. 2006), suggesting that most of the energy is dissipated by creep events consistently with observations from (Gross et al. 1993) who showed that only 3% of the fracture energy is radiated and from (Kanamori and Anderson 1975) for earthquake dynamics where the radiated energy is always negligible in front of the seismic moment ($M_0/E \approx 1/20,000$, where M_0 is the seismic moment describing the total dissipated energy and *E* the radiated energy).

The last input from the experiment is the comparison of the optical events and acoustic emissions during the load perturbation. Figure 11 shows how both families of events are



synchronous which clearly suggests that acoustic emissions are directly controlled by the large-scale creeping process.

Conclusions

Observations at the Soultz-sous-Forêts EGS site of aseismic slips that are synchronous with micro-seismic events located in multiplets (Bourouis and Bernard 2007; Cornet et al. 1997) suggest that both processes co-exist within the same fault zones during a fluid injection period. Here we proposed an experimental model that directly supports this observation. Our model is built on the interfacial failure along a heterogeneous weak plane and combines creep failure and brittle rupture without fluid. Experimental observations are numerous and consistent with large-scale measurements. They provide clear hints on the processes involved at the asperity scale. Our conclusion is therefore that fluids are not necessarily the driving force of the fault activity in terms of pore pressure. They might have rather a role on local creep acceleration because of their effect on subcritical crack growth. An interesting perspective would be to estimate the evolution of the permeability owing to aseismic slip.

Competing interests

The authors declare that they have no competing interests.

Authors' contributions

JS conceived of the study, drafted the manuscript and paraticipated to the coordianation. OL performed the experimental study. FC conceived the field experiment. FC, NC and AG participated to the integration of the field results in the study. All authors read and approved the final manuscript.

Acknowledgements

We thank J. Elkhoury, J.P. Ampuero, R. Toussaint, A. Cochard, M. Bouchon, H. Karabulut, K.J. Maloy, A. Stormo, A. Hansen, M. Grob, and G. Daniel for fruitful discussions; A. Steyer for technical support; and two anonymous reviewers for very constructive comments. This work has been published under the framework of the LABEX ANR-11-LABX-0050-G-EAU-THERMIE-PROFONDE and benefits from a funding from the state managed by the French National Research Agency as part of the 'Investments for the Future' program.

Author details

¹EOST, Université de Strasbourg/CNRS, 5 rue René Descartes, 67000 Strasbourg, France. ²GEIE EMC, Route de Soultz-sous-Forêts, 67250 Kutzenhausen, France. ³ES-Géothermie, 3, Chemin du Gaz, 67500 Haguenau, France.

Received: 26 June 2014 Accepted: 20 October 2014 Published online: 16 December 2014

References

- Abercrombie R, Leary P (1993) Source parameters of small earthquakes recorded at 2.5 km depth, Cajon Pass, Southern California: implications for earthquake scaling. Geophys Res Lett 20(14):1511–1514
- Bourouis S, Bernard P (2007) Evidence for coupled seismic and aseismic fault slip during water injection in the geothermal site of Soultz (France), and implications for seismogenic transients. Geophys J Int 169(2):723–732
- Burov EB (2009) Plate rheology and mechanics. In: Watts AB (ed) Crust and lithosphere dynamics. Treatise on geophysics. Elsevier, Amsterdam. pp 99–151
- Charléty J, Cuenot N, Dorbath L, Dorbath C, Haessler H, Frogneux M (2007) Large earthquakes during hydraulic stimulations at the geothermal site of Soultz-sous-Forêts. Int J Rock Mech Min Sci 44(8):1091–1105
- Cornet F, Bérard T, Bourouis S (2007) How close to failure is a granite rock mass at a 5 km depth Int J Rock Mech Min Sci 44(1):47–66
- Cornet FH, Helm J, Poitrenaud H, Etchecopar A (1997) Seismic and aseismic slips induced by large-scale fluid injections. Pure Appl Geophys 150:563–583
- Cuenot N, Dorbath C, Dorbath L (2008) Analysis of the microseismicity induced by fluid injections at the EGS site of Soultz-sous-Forêts (Alsace, France): implications for the characterization of the geothermal reservoir properties. Pure Appl Geophys 165(5):797–828
- Dorbath L, Cuenot N, Genter A, Frogneux M (2009) Seismic response of the fractured and faulted granite of Soultz-sous-Forêts (France) to 5 km deep massive water injections. Geophys J Int 177(2):653–675
- Genter A, Castaing C, Dezayes C, Tenzer H, Traineau H, Villemin T (1997) Comparative analysis of direct (core) and indirect (borehole imaging tools) collection of fracture data in the hot dry rock Soultz reservoir (France). J Geophys Res Solid Earth 102(B7):15419–15431

Genter A, Evans K, Cuenot N, Fritsch D, Sanjuan B (2010) Contribution of the exploration of deep crystalline fractured reservoir of Soultz to the knowledge of enhanced geothermal systems (EGS). Comptes Rendus Geoscience 342(7):502–516

Grob M, Schmittbuhl J, Toussaint R, Rivera L, Santucci S, Jøy KJM (2009) Quake catalogs from an optical monitoring of an interfacial crack propagation. PAGEOPH 166(5–7):777–799

Gross SP, Fineberg J, Marder M, McCormick W, Swinney HL (1993) Acoustic emissions from rapidly moving cracks. Phys Rev Lett 71(19):3162

Häring MO, Schanz U, Ladner F, Dyer BC (2008) Characterisation of the basel 1 enhanced geothermal system. Geothermics 37(5):469–495

Helm J (1996) The natural seismic hazard and induced seismicity of the european HDR (hot dry rock) geothermal energy project at Soultz-sous-Forêts, France. PhD thesis

Huenges E, Ledru P (2010) Geothermal energy systems: exploration, development, and utilization. John Wiley & Sons, Weinheim

Jaeger JC, Cook NG, Zimmerman R (2009) Fundamentals of rock mechanics. Backwell Publishing, Australia

Kanamori H, Anderson DL (1975) Theoretical basis of some empirical relations in seismology. Bull Seismol Soc Am 65(5):1073–1095

Kaneko Y, Avouac J-P, Lapusta N (2010) Towards inferring earthquake patterns from geodetic observations of interseismic coupling. Nat Geosci 3(5):363–369

Lengliné O, Toussaint R, Schmittbuhl J, Elkhoury JE, Ampuero J, Tallakstad KT, Santucci S, Måløy KJ (2011a) Average crack-front velocity during subcritical fracture propagation in a heterogeneous medium. Phys Rev E 84(3):036104

Lengliné O, Schmittbuh J, Elkhoury J, Ampuero J-P, Toussaint R, Måløy KJ (2011b) Downscaling of fracture energy during brittle creep experiments. J Geophys Res Solid Earth 116(B8)

Lengliné O, Elkhoury J, Daniel G, Schmittbuhl J, Toussaint R, Ampuero J-P, Bouchon M (2012) Interplay of seismic and aseismic deformations during earthquake swarms: an experimental approach. Earth Planet Sci Lett 331:215–223

Majer EL, Baria R, Stark M, Oates S, Bommer J, Smith B, Asanuma H (2007) Induced seismicity associated with enhanced geothermal systems. Geothermics 36(3):185–222

Måløy KJ, Santucci S, Schmittbuhl J, Toussaint R (2006) Local waiting time fluctuations along a randomly pinned crack front. Phys Rev Lett 96(4):045501

Sausse J, Dezayes C, Dorbath L, Genter A, Place J (2010) 3d model of fracture zones at Soultz-sous-Forêts based on geological data, image logs, induced microseismicity and vertical seismic profiles. Comptes Rendus Geoscience 342(7):531–545

Schmittbuhl J, Delaplace A, Maloy KJ, Perfettini H, Vilotte JP (2003) Slow Crack Propagation and Slip Correlations. Pure Appl Geophys 160:961–976

Schmittbuhl J, Måløy KJ (1997) Direct observation of a self-affine crack propagation. Phys Rev Lett 78(20):3888

Shapiro SA, Audigane P, Royer J-J (1999) Large-scale *in situ* permeability tensor of rocks from induced microseismicity. Geophys J Int 137(1):207–213

Vilarrasa V, Carrera J, Olivella S (2013) Hydromechanical characterization of co₂ injection sites. Int J Greenhouse Gas Control 19:665–677

doi:10.1186/s40517-014-0014-0

Cite this article as: Schmittbuhl et al.: Induced seismicity in EGS reservoir: the creep route. Geothermal Energy 2014 2:14.

Submit your manuscript to a SpringerOpen[®] journal and benefit from:

- ► Convenient online submission
- ► Rigorous peer review
- Immediate publication on acceptance
- Open access: articles freely available online
- High visibility within the field
- Retaining the copyright to your article

Submit your next manuscript at > springeropen.com